Material Safety Data Sheet	U.S. Department of Labor								
May be used to comply with OSHA's Hazard Communication Standard				ety and Health A	dministration				
29 CFR 1910.1200. Standard must be		(Non-Mandatory Form) Form Approved							
consulted for specific requirements.		OMB No. 1218-0072							
Identity (As Used on Label and List)  BUTANE	1	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to							
			indicate that.						
SECTION 1									
Supplier's Name	MASSAMACKA			Emergency Telephone Number					
Bernz-O-matic		585-798-4949							
Address Number, Street, City, State and ZIP Code		Telephone Number for Information 585-798-4949							
	1	Date Prepared							
One BernzOmatic Drive		November 10, 2005							
Medina, NY 14103		Signature of Preparer (Optional)							
SECTION II Hagardays Ingredients / Ic	lantity Inform	nation		a Charles and Charles					
SECTION II - Hazardous Ingredients / Id	ientity infort	nation	4889		Other Limits				
Hazardous Components Specific Chemical Identity, Common Name(s)		OSHA PEL		ACGIH TLV	Recommended	% (optional)			
Butane C <sub>4</sub> H <sub>10</sub>				800 ppm					
NFPA HAZARD RATINGS		HMIS RATINGS							
Health		Health							
Flammability		Flammability							
Reactivity		Reactivity							
Notes:									
SECTION III - Physical / Chemical Char	racteristics								
Boiling Point	440=		Specific Gravity (H <sub>2</sub> 0 - 1)						
	11°F		.58						
Vapor Pressure (mm Hg)			Mel	ting Point	127270				
	31 PSIG @				N/A				
Vapor Density (AIR=1)			Evaporation Rate						
	2.0		But	yl Acetate -1)	N/A				
Solubility in Water									
	Negligible								
Appearance and Odor									
	Colorless	<ul><li>Rotten</li></ul>	Egg	g (Sulfur) Oc	lor				
SECTION IV - Fire and Explosion Hazar	d Data								
Flash Point (Method Used)		Flammable Limits		e Limits	LEL	UEL			
	-101°F				1.8	8.4			
Extinguishing Media									
CO <sub>2</sub> , Foam, Class "B" or "C" Extinguishers									
Special Fire Fighting Procedures									
Use Water to Cool Tanks									
Unusual Fire and Explosion Hazards									
Heavier than air (Vapor density 2.0). May travel a considerable									
distance to an ignition source and flash back.									

SECTION V - Reactivity	Data							
Stability → Unstable Stable X	Conditions to Avoid							
Incompatibility (Materials to Av	oid)							
N/A								
Hazardous Decomposition or By	products							
		N/A						
	lay Occur Not Occur X							
SECTION VI - Health Ha	azard Data							
Routes of Entry →	Inhalation?	Skin? Ingestion? YES NO						
Health Hazards (Acute and Chronic)								
\$	Burning the fuel	l may car	use Carbon Mo	onoxide (CO)				
Carcinogenicity →	NTP? N/A		IARC Monographs?		OSHA Regulated? N/A			
Signs and Symptoms of Exposur								
	Simple asphyxia	ant. Expo	sure to liquid	may cause f	rost burn.			
Medical Conditions Generally Aggravated by Exposure  N/A								
Emergency and First Aid Procedu		AS DAVID UTCH	32					
Remove person to fresh air.								
Warning	TI. 6 1				I			
This fuel, and byproducts of combustion of this fuel, contain chemicals								
				ıse cancer, b	irth defects, and			
	other reproduct	ive harm	1.					
SECTION VII - Precautions for Safe Handling and Use								
Steps to be Taken in Case Material is Released or Spilled								
Remove ignition sources and ventilate area.								
Waste Disposal Method					ř.			
Precautions to be Taken in Hand				15 19 1921				
	Store out of dir	rect sun	ight at temper	atures below	v 120°F.			
Other Precautions	None							
SECTION VIII - Control	Measures							
Respiratory Protection (Specify T	ype) Not required w	ith norm	al use.					
Ventilation	Local Exhaust		ical (General) N/A	Special N/A	Other N/A			
Protective Gloves			Eye Protection					
Not required			Safety glasses recommended					
Other Protective Clothing or Equ Not required								
Work / Hygienic Practices			-12-1					
	Information	Editoria de la como		A 1527652/A45319 A1				
SECTION IX - Shipping WHMIS Classification: A-Com		mmahla	Class: 2.1					
Gas	ipressed Gas & BI-Fla	шпане	Class: 2.1					
DOT	Proper Shipping Name Butane		Hazard Classification Flammable Gas		UN. No. 1011			