

# Sparkular Machine and Product



## Part No.: Machine BT02

### Parameters:

Dimension: 7.87" W × 8.46" D × 11.22" H

Weight: 18.73 Lbs

Input: 110VAC, 50/60Hz

Work Power: 400w

Work Temp. : -4 degrees F – 158 degrees F

Casing: Flame Retardant Plastic

Fountain Height: 1.0m ~ 5.0m

Fountain angle to ground: 45°~90°

Warranty: 1 year

Life Expectancy: > 5 years

**The Sparkular Machine is fully adjustable in Height and duration. It can be controlled with its own console or on a Standard DMX console using 2 channels per Fixture. Must maintain a 10' separation to audience.**

## Sparkular Granules Part No.: HC8200

### Parameters:

Zirconium and Titanium alloy, with 80% Zirconium and 20% Titanium

Powder Mesh number: 80-100, Diameter: 180um to 250um

Weight: 200 gr/Pouch

Use Time: 15 minutes (at 100%) /Pouch

Working Temperature: -4 degrees F – 158 degrees F

Packaging: 12 Pouches/Box – 12 Boxes / Case



**The Sparkular Granules are a proprietary mixture of Metals. The 200 grams will last 15 minutes at full height and full density. Each pouch comes with an RFID Card that allows a 25 minute run time. The materials will not rust or cause any discoloration.**